
	DECLARATION OF PERFORMANCE MANUFACTURER: ABC WINDOWS ADDRESS: 123 THE GROVE ANYTOWN ANY POST CODE LAST 2 DIGITS OF YEAR OF CE MARKING : 13
PRODUCT TYPE	CASEMENT WINDOW
MANUFACTURERS REFERENCE No	SPW600 SERIES
INTENDED USE	OPENABLE WINDOW FOR VENTILATION ONLY
AUTHORISED REPRESENTATIVE	SENIOR ARCHITECTURAL SYSTEMS
AVCP SYSTEM	3
REACTION TO FIRE (ROOF WINDOWS ONLY)	NPD (NO PERFORMANCE DECLARED)
EXTERNAL FIRE PERFORMANCE (ROOF WINDOWS ONLY)	NPD
RESISTANCE TO SNOW AND PERMANENT LOAD (ROOF WINDOWS ONLY)	NPD
HARMONISED PRODUCT STANDARD	BS EN 14351-1
DECLARED PERFORMANCE OF EACH CHARACTERISTIC : <u>MANDATORY IN RED</u>	
THERMAL TRANSMITTANCE	1.7 W/M2K
AIR PERMEABILITY	NPD OR PERFORMANCE e.g. 600Pa CLASS 3
WATERTIGHTNESS	NPD OR PERFORMANCE e.g. 600Pa CLASS 3
RESISTANCE TO WINDLOAD	NPD OR PERFORMANCE e.g. 2400Pa CLASS 3
DANGEROUS SUBSTANCES	NONE, SEE NOTE BELOW
ACOUSTICS	NPD OR PERFORMANCE e.g. 34Rw
LOAD BEARING CAPACITY OF SAFETY DEVICES	e.g. 350N,PASS OR NONE FITTED
IMPACT RESISTANCE OF GLASS OR FRAGMENTAL MATERIAL	NPD OR PERFORMANCE FROM GLASS SUPPLIER
RADIATION PROPERTIES	NPD OR PERFORMANCE FROM GLASS SUPPLIER
SIGNED FOR AND ON BEHALF OF THE MAUFACTURER : PRINT NAME : JOB TITLE : DATE OF ISSUE :	 RICHARD HEAD MANAGING DIRECTOR 18-04-2013

Note: "Senior Architectural Systems declare that our products, which are used in the manufacture of windows, doors and curtain walling, are safe in use and will not emit dangerous substances, compounds or particles into indoor or outdoor air, or release dangerous substances into drinking water, ground, or marine waters or soil"