

PUR^e® FOLD Folding Sliding Door System

Technical Datasheet

Scope

The PUR^e® FOLD Folding Sliding door system has been designed to meet current and future building regulations, with impressive U-values and thermal performances. PUR^e® is an evolved generation of aluminium window and door systems manufactured in the UK. It combines the long life and low maintenance of aluminium with a patented high insulation PUR foam thermal barrier. PUR^e® FOLD Folding Sliding doors are capable of accepting glazing up to 48mm thick.

Materials

- Extruded aluminium is generally Aluminium Alloy 6060.T6/T66, 6063.T6/T66, 6082.T6 to BS EN 755-9 and EN 12020-2.
- Polyamide thermal barriers are manufactured in accordance with PA66 GF25.
- The Gasketry is generally manufactured in accordance with BS ISO 3302-1.
- The fixings are generally A2 Stainless Steel screws.

Finishes

PUR^e® FOLD Folding Sliding door sections are available typically in two finishes.


- Polyester Powder Coating to BS EN 12206-1 Part 1 painted in house. Surface finished to a minimum of 40 microns standard, or enhanced to suit project requirements, in accordance with ISO 9001, ISO 14001 and ISO 45001.
- Anodised finishes are to BS3897 to a minimum of 25 microns (AA25), supplied in either satin or polished finish in a limited range of colours.

Construction

PUR^e® is constructed using mitred corners and/or shear blocks, joined with crimped or mechanical cleats; alignment chevrons assist in clean, accurate mitres. A proprietary sealant is used on all metal joints in line with good practice.

Environmental

Senior Architectural Systems is fully compliant with BS EN ISO 9001, BS EN ISO 14001, ISO 45001 and BES6001 standards. When used on projects involved in a BREEAM assessment, or within the Code for a Sustainable Built Environment, (which therefore involves the Green Guide specification) can offer significant benefits. For project specific assistance, please contact our specification team.



**Image for indicative purposes only*

Typical Sizes

Max door leaf width	1000mm
Max door leaf height	2616mm
Max outerframe height	2700mm
Max weight per door leaf	100kg

*Average U-values

CEN standard (Double Glazed)	1.3 W/m ² K
CEN standard (Triple Glazed)	0.88 W/m ² K

Glazing

Thickness	24mm - 48mm
-----------	-------------


Testing

Security	PAS24 & SBD
**BS6375 -1	✓
BS6375 - 2	✓

*All calculations are based on CEN sized single doors 1230mm x 2180mm ±25% and double door 2000mm x 2180mm ±25%.

** Results may vary based on specification. Further details are available upon request.

Test certifications available upon requests, please contact.



Secured by Design



Senior Architectural Systems Ltd, Eland Road, Denaby Main, Doncaster, South Yorkshire, DN12 4HA.
Tel: 01709 772 600 E-mail: info@sasmail.co.uk www.seniorarchitectural.co.uk

Due to a policy of continual product development, Senior Architectural Systems reserves the right to alter any of the specifications given in this publication without prior notice. The specification for any given application must be checked with Senior Architectural Systems prior to manufacture. No responsibility for accuracy is accepted by Senior Architectural Systems. Always refer to the Technical Manual.